

	dimensions STD (mm)		thic door	frame tolerances	dimension free passage (mm)		structural opening (mm)	
	height	width			height	width	height	width
portaro®	2000 / 2100 2300 / 2500	750-850-950	35	< 100mm [-0;+ 0] ≥ 100mm [-5;+10]	door height -1,5	door width - 49	door height + 35	door width + 70
portaro® rebated	2010 / 2110 2310 / 2510	776-876-976	40	< 100mm [-0;+ 0] ≥ 100mm [-5;+10]	door height -14,5	door width - 43	door height + 25	door width + 45
portaro® sliding outside wall	2000 / 2100 2300 / 2500	850-950-1050	35	< 100mm [-0;+ 0] ≥ 100mm [-5;+10]	door height -24	door width - 115	door height + 10	door width - 30
portaro® inverse	2010 / 2110 2310 / 2510	776-876-976	47	< 100mm [-0;+ 0] ≥ 100mm [-5;+10]	door height - 3,5	door width - 61	door height + 65	door width +115
portaro® pivotal	2000 / 2100 2300 / 2500	750-850-950	44	< 100mm [-0;+ 0] ≥ 100mm [-5;+10]	door height -1,5	door width - 53	door height + 35	door height + 70
portaro® E15	2000 / 2100	750-850-950	40	≥ 90mm [-5;+10]	door height - 6	door width - 54	door height + 45	door height +85
portaro® EI30	2000 / 2100	750-850-950	44	≥ 90mm [-5;+10]	door height - 6	door width - 63	door height + 50	door height +100
portaro® inverse EI30*	2000 / 2040	776-876-976	47	≥ 90mm [-5;+10]	door height - 3,5	door width - 61	door height + 65	door width +115
portaro® EI30 AC 33dB	2000 / 2100 2300	750-850-950	44	≥ 90mm [-5;+10]	door height - 6	door width - 63	door height + 50	door width +100
portaro® EI30 AC 37dB	2000 / 2100 2300	750-850-950	54	≥ 90mm [-5;+10]	door height -15	door width - 82	door height + 50	door width +100
portaro® EI30 AC 42dB	2000 / 2100 2300	750-850-950	57	≥ 90mm [-5;+10]	door height -15	door width - 84	door height + 65	door width +115
portaro® EI60*	2000 / 2100	850-950	54	≥ 100mm [-0;+10]	door height - 6	door width - 71	door height + 70	door width +125
portaro® security	2000 / 2100	850-950	44	≥ 90mm [-5;+10]	door height - 6	door width - 63	door height + 50	door width +100
portaro® SBD*	2000 / 2040	850-950	44	≥ 90mm [-5;+10]	door height - 16	door width - 71	door height + 50	door width +100
portaro® entrance	2000 / 2100	850-950	44	≥ 90mm [-5;+10]	door height - 6	door width - 63	door height + 50	door width + 90

The dimensions of the products may be changed without prior notice.
For doors and frames of 2040mm in height, the maximum door width is 926mm
Other dimensions are subject to availability.
The dimensions of the free passage way consider the door to be open at a 90°ba angle.
Size tolerance +- 3mm.

The dimensions of the products may be changed without prior notice.