

# FD30(S) 44MM

## STANDARD DUTY CORE

TECHNICAL SHEET

### FIRE RATING

FD30(S) Solid core 44mm to BS 476 Part 22:1987, when intumescent seals or intumescent/smoke seals are fitted to door leaf or door frame/lining as test certification (details on request). Fitted 'Q' mark fire plug (BM TRADA) and also Certifire label (BWF - Fire Door Alliance).

### DURABILITY

Tested to severe duty BS EN 1192/DD171 Class 4

### DOOR

Overall 44 mm thick

Solid core in particle board

Single stile 33mm (nominal) softwood each edge FSC

Two number rails 70mm (nominal) in total, softwood FSC top and bottom of the door

Substrate with 3.2mm MDF-controlled material internal quality, or hardboard at our discretion

Lippings 6mm (nominal) hardwood to vertical edges (concealed by face) requires finishing on site after sizing.

Optional edge banding available MTO except for Lacdor Satin white, Visual Sensations CDW Alpine and Forest, which are edge banded and unlipped as standard.

### FINISHES

Naturdor® - Real wood veneer, Stained real wood veneer and/or with design

Dekordor® 3D - Embossed grain effect finish

Dekordor® HD - Heavy Duty, continuous pressure laminate (CPL)

Dekordor® SD - Standard Duty, finish foil

Lacdor - Satin white or white lacquered

### OPTIONS

Factory glazing - If required and as specified in accordance with test certification. Max 1.2 m<sup>2</sup> total area. Glazed 7mm clear glass.

Grooves and inlays - Where required can be applied in horizontal and vertical designs

Oversized doors

### PACKAGING

Cardboard one side and polythene wrapped apart from primed and paintgrade which are unwrapped.

### DOOR KIT AND SET SYSTEMS

This product may be used in conjunction with a Vicaima Portaro® or Easi-Fit door kit system.

**Please note:** Some specific finishes/ranges may differ slightly from the information shown above, please check with our Technical Department for further details.



**FD30**

### DOOR CONSTRUCTION



**Note:** Door image represents core construction only and not face finish



**Notes:** Depending on product features or configurations, dimensions will vary. As we are constantly improving our product range, we reserve the right to make changes without prior notice. The guarantee certificate is an integral part of the technical data sheet, available at [www.vicaima.com](http://www.vicaima.com)