

FD60 54MM

VCP HIGH DENSITY CORE

TECHNICAL DATA SHEET

FIRE RATING

FD60 high density core 54mm according to BS476 Part 22:1987

ACOUSTIC

Fully caulked door tested for acoustic insulation up to 35dB as per ISO 717-1 standard.

DURABILITY

Tested to severe duty BS EN 1192

DOOR

Overall 54mm thick

Vicpan®60 high density core

Lippings in hardwood all edges (concealed by face) requires finishing on site after sizing.

FINISHES

Naturdor® - Real wood veneer, Stained real wood veneer

Dekordor® 3D - Embossed grain effect finish

Dekordor® HD - Heavy Duty, continuous pressure laminate (CPL)

Dekordor® SD - Standard Duty, finish foil

Laccor - Satin white or white lacquered

OPTIONS

Factory glazing - If required and as specified in accordance with test certification. Max 0.76 m² total area. Glazed 10mm clear fd60 glass.

"V" groove 3X1.5mm or inlays (vertical)

Approved automatic drop seal

DOOR KIT AND SET SYSTEMS

This product may be used in conjunction with a Vicaima Portaro® system.

Please note: Some specific finishes/ranges may differ slightly from the information shown above, please check with our Technical Department for further details.



FD60

DOOR CONSTRUCTION



Note: Door image represents core construction only and not face finish